

KIT PER DISTRIBUZIONE GRASSO PER FUSTI GREASE DISPENSING KITS FOR DRUMS



| Codice Code ref. | Per fusti Suitable for drums | Grasso Grease | Distanza Distance |
|---------------------|---------------------------------|---|--|
| 85.03 | 20÷30 kg | Adatto per tutti i tipi di grasso Suitable for all types of grease | Medie e lunghe dist. Short & long dist. |
| 85.05 | 50÷60 kg | Adatto per tutti i tipi di grasso Suitable for all types of grease | Medie e lunghe dist. Short & long dist. |
| 85.08 | 180÷220 kg | Adatto per tutti i tipi di grasso Suitable for all types of grease | Medie e lunghe dist. Short & long dist. |

Il kit comprende:
The kit includes:

| Codice Code ref. | Pompa Pump | Carrello Trolley | Coprifusto Drum Cover | Membrana Follower Plate | Tubo Hose | Pistola Gun |
|---------------------|---------------|---------------------|--------------------------|----------------------------|--------------|----------------|
| 85.03 | 85.03-A | 85.03-C | 85.03-F | 85.03-D | 85.03-T03 | 85.03-P |
| 85.05 | 85.05-A | 85.05-C | 85.05-F | 85.05-D | 85.03-T03 | 85.03-P |
| 85.08 | 85.08-A | 85.08-C | 85.08-F | 85.08-D | 85.03-T03 | 85.03-P |

Per una maggiore durata ed efficienza delle pompe è consigliabile utilizzare aria essiccata o montare un filtro sulla linea in entrata (optional avente cod. 85.03-R, vedi più avanti negli accessori)
It is recommended to use dried air or to put an inlet filter to guarantee more efficient and lasting long to the pneumatic pumps (having code ref. 85.03-R, see in next section of the accessories)

POMPE PNEUMATICHE PER GRASSO - AEROPULSOMETRI GREASE PNEUMATIC PUMPS



| Codice Code ref. | Fusti Drums | Rapporto Ratio | Portata a 6 bar Flow rate at 6 bar | Pressione di lavoro Working pressure | Pescante (mm) Shank (mm) | Ingresso Inlet | Uscita Outlet |
|---------------------|----------------|-------------------|---|---|-----------------------------------|-------------------|------------------|
| 85.03-A | 20÷30 kg | 50:1 | 1500 g/min | 6÷8 bar | Ø 28; L 480 | F 1/4" | M 1/4" |
| 85.05-A | 50÷60 kg | 50:1 | 1500 g/min | 6÷8 bar | Ø 28; L 740 | F 1/4" | M 1/4" |
| 85.08-A | 180÷220 kg | 50:1 | 1500 g/min | 6÷8 bar | Ø 28; L 940 | F 1/4" | M 1/4" |

Caratteristiche:
Rapporto 50:1 adatto per la distribuzione di tutti i tipi di grasso (NLGI 000÷6) a brevi e lunghe distanze sia su carrellati che su impianti fissi

Features:
Ratio 50:1 pump suitable for transferring all type of grease (000÷6 NLGI) at short & long distances for portable & wall mounted grease kits

Per una maggiore durata ed efficienza delle pompe è consigliabile utilizzare aria essiccata o montare un filtro sulla linea in entrata (optional avente cod. 85.03-R, vedi più avanti negli accessori)
It is recommended to use dried air or to put an inlet filter to guarantee more efficient and lasting long to the pneumatic pumps (having code ref. 85.03-R, see in next section of the accessories)

ACCESSORI PER POMPE PNEUMATICHE GRASSO ACCESSORIES FOR GREASE PNEUMATIC PUMPS



COPRIFUSTO/DRUM COVER

| Codice Code ref. | Fusti Drums | Ø est. fusto Drum O.D. | Ø Coperchio Cover Ø | Ø Bocchettone Union Ø |
|---------------------|----------------|---------------------------|------------------------|--------------------------|
| 85.03-F | 20÷30 kg | 260÷350 mm | 330 mm | 28 mm |
| 85.05-F | 50÷60 kg | 340÷385 mm | 400 mm | 28 mm |
| 85.08-F | 180÷220 kg | 550÷600 mm | 600 mm | 28 mm |



MEMBRANA PREMIGRASSO/FOLLOWER PLATE

| Codice Code ref. | Fusti Drums | Ø int. fusto Drum I.D. | Ø Membrana Diaphragm Ø | Ø Bocchettone Union Ø |
|---------------------|----------------|---------------------------|---------------------------|--------------------------|
| 85.03-D | 20÷30 kg | 250÷300 mm | 310 mm | 28 mm |
| 85.05-D | 50÷60 kg | 335÷400 mm | 400 mm | 28 mm |
| 85.08-D | 180÷220 kg | 540÷580 mm | 600 mm | 28 mm |

**ACCESSORI PER POMPE PNEUMATICHE GRASSO (segue)
ACCESSORIES FOR GREASE PNEUMATIC PUMPS (follows)**



**TUBI FLESSIBILI DI COLLEGAMENTO PER GRASSO
GREASE CONNECTION FLEXIBLE HOSES**

| Codice Code ref. | Lunghezza Length |
|---------------------|---------------------|
| 85.03-T01 | 1,5 m |
| 85.03-T03 | 3 m |
| 85.03-T05 | 5 m |
| 85.03-T10 | 10 m |
| 85.03-T15 | 15 m |
| 85.03-T18 | 18 m |
| 85.03-T20 | 20 m |

Descrizione
Description

Tubi flessibili di collegamento per grasso, diam. int. 1/4", SAE 100 R2AT, pressione d'esercizio 600 bar, raccordi F/F 1/4"G.

Grease connection flexible hoses, internal diameter size 1/4", SAE 100 R2AT, working pressure 600 bar, fittings F/F 1/4"G.



**PISTOLA GRASSO CON TUBO FLESSIBILE
GREASE GUN WITH FLEXIBLE HOSE**

| Codice Code ref. | Cod. Tubo Pipe code | Ingresso Inlet port | Testina a 4 griffe 4 jaws coupler |
|---------------------|------------------------|------------------------|--------------------------------------|
| 85.03-P | 81.07 | F 1/4" | 81.73-ZB |

Caratteristiche:
Comprendente di tubo in gomma L=300mm e testina a 4 griffe
Features:
Including 300mm rubber hose & 4 jaw Coupler

**PISTOLA GRASSO CON TUBO RIGIDO
GREASE GUN WITH RIGID HOSE**

| Codice Code ref. | Cod. Tubo Pipe code | Ingresso Inlet port | Testina a 4 griffe 4 jaws coupler |
|---------------------|------------------------|------------------------|--------------------------------------|
| 85.03-TR | 81.22 | F 1/4" | 81.73-ZB |

Caratteristiche:
Comprendente di tubo in acciaio L=150mm e testina a 4 griffe
Features:
Including 150mm steel hose & 4 jaw Coupler

**PISTOLA GRASSO
GREASE GUN**

| Codice Code ref. | Ingresso Inlet port |
|---------------------|------------------------|
| 85.03-PN | F 1/4" |

**TUBO FLESSIBILE PER PISTOLA
FLEXIBLE HOSE FOR GUN**

| Codice Code ref. | Lunghezza Length | Raccordi Part |
|---------------------|---------------------|------------------|
| 81.07 | 300 mm | M10x1 |

**TESTINA IDRAULICA A 4 GRIFFE
4 JAW HYDRAULIC COUPLER**

| Codice Code ref. | Raccordo Part | Conf. Standard Standard pack. |
|---------------------|------------------|----------------------------------|
| 81.73-ZB | M10x1 | 25 pz/ pcs |

**RACCORDO GIREVOLE DI SNODO
SWIVEL JOINT**

| Codice Code ref. | Raccordo Part |
|---------------------|------------------|
| 85.03-S | 1/4" M-M |

**RACCORDO GIREVOLE DI SNODO TRIPLO
TRIPLE SWIVEL JOINT**

| Codice Code ref. | Raccordo Part |
|---------------------|------------------|
| 85.03-ST | 1/4" M-M |

**FILTRO REGOLATORE
FILTER & REGULATOR**

| Codice Code ref. | Raccordo Part |
|---------------------|------------------|
| 85.03-R | 1/4" |

Regolatore di pressione con attacchi femmina da G 1/4" con manometro, filtro con unità di drenaggio condensa semi-automatico e nebulizzatore d'olio.
Pressure regulator, G 1/4" female ports, with pressure gauge, filter with semi-automatic condensate drainage unit & oil atomizer.

**CARRELLO PORTA FUSTI
TROLLEY FOR DRUMS**

| Codice Code ref. | Fusti Drums | Ruote ant. Front Wheels | Ruote post. Rear Wheels | Dimensione base Base dimension |
|---------------------|----------------|----------------------------|----------------------------|-----------------------------------|
| 85.03-C | 20÷30 kq | 2 fisse/ fixed | 2 piroett./ swivel | 310x310 mm |
| 85.05-C | 50÷60 kq | 2 fisse/ fixed | 2 piroett./ swivel | 410x410 mm |
| 85.08-C | 180÷220 kq | 2 fisse/ fixed | 2 piroett./ swivel | 620x620 mm |

